

Front



## STASIUN PENYEDIA LISTRIK UMUM (SPLU)



Standing / Tower



Hook / Pole mounted



Hang / Wall Mount



Stall / Pedestal

### PT. SYMPHOS ELECTRIC

Jl. Raya Agarindo No. 10 Kel. Bunder Kec. Cikupa, Tangerang - Banten  
 Phone : +62-21 5471 2089, 5971 2089, 5971 2609 - Fax. : +62 21 5471 2039  
 Email : marketing@symphos-weltraf.com  
[www.symphoselectric.com](http://www.symphoselectric.com)

Made In Indonesia

Back

## SPEKIFIKASI MEKANIK & ELECTRIK



Spesifikasi Mekanik	Standing / Tower	Hook / Pole mounted	Hang / Wall Mount	Stall / Pedestal
Selungkup	Plat SPCC, Tebal minimum 2 mm	Plat SPCC, Tebal minimum 2 mm	Plat SPCC, Tebal minimum 1 mm	Pipa Schedule
Dimensi	1500 x 520 x 520 ( H x W x D - Terluar )	600 x 560 x 336 ( H x W x D - Terluar )	450 x 330 x 180 ( H x W x D - Terluar )	1725 x 225 ( H x Dia. )
Cat	Powder Coating & Branding corporate PLN	Powder Coating & Branding corporate PLN	Powder Coating & Branding corporate PLN	Powder Coating & Branding corporate PLN
IP	IP 44	IP 44	IP 44	IP 44
Spesifikasi Elektrik				
Tegangan	230/400 V	230/400 V	230/400 V	230/400 V
Frekuensi	50 Hz	50 Hz	50 Hz	50 Hz
Saklar Utama	RCBO 1P + N, In 25 A, Ie 30 mA	RCBO 1P + N, In 25 A, Ie 30 mA	RCBO 1P + N, In 25 A, Ie 30 mA	RCBO 1P + N, In 25 A, Ie 30 mA
Keypad	Stainless Steel, Minimum IP 44, Anti Vandalism	Stainless Steel, Minimum IP 44, Anti Vandalism	Stainless Steel, Minimum IP 44, Anti Vandalism	Stainless Steel, Minimum IP 44, Anti Vandalism
Kotak Kontak	Outdoor, 16 A, IP 67	Outdoor, 16 A, IP 67	Outdoor, 16 A, IP 67	Outdoor, 16 A, IP 67
Pentanahan	Ground Rod diameter 16 mm & Kabel BC 10 mm <sup>2</sup>	Ground Rod diameter 16 mm & Kabel BC 10 mm <sup>2</sup>	Ground Rod diameter 16 mm & Kabel BC 10 mm <sup>2</sup>	Ground Rod diameter 16 mm & Kabel BC 10 mm <sup>2</sup>
Penerangan	LED Strip	LED Strip	LED Strip	LED Strip

